

SAFETY DON'T'S

- DON'T stand above the highest **safe standing level**
- DON'T stand above the second step from the top of a stepladder and the 4th rung from the top of an extension ladder. A person standing higher may lose their balance and fall.



INDUSTRIAL DUTY ALUMINUM MULTI-WAY LADDERS (2700 SERIES)

CSA grade 1,

ANSI type 1 - 250-lb. Load Rating

- Easily converts and locks securely and safely into all positions
- Durable extruded aluminum rails and slip resistant serrated steps and rungs
- Fixed rubber safety shoes on front section
- Swivel rubber shoes on rear section
- ABS, high impact, non-marring end caps

MF402



FEATHERLITE
INDUSTRIAL LADDERS

Model No.	Nominal Height'	Extension Ladder Height'	Maximum Extension Open Length'	Wt. lbs.	Price /Each
MF402	6	12	9	22	
MF403	7	14	11	25	
MF404	8	16	13	28	

INDUSTRIAL HEAVY-DUTY 2-WAY STEPLADDERS (3600 SERIES)

CSA grade 1A,

ANSI type 1A - 300-lb. Load Rating

- Double-front construction allows access from either side
- 3" serrated steps and side rails
- Features extra thick top brackets for greater stability; "J" shape spreader arms and heavy-duty rubber safety shoes

VC319



FEATHERLITE
INDUSTRIAL LADDERS

Model No.	Nominal Height'	Base Width"	Spread"	Wt. lbs.	Price /Each
VC318	4	19	39	14	
VC319	6	21	57	20	
VC320	8	24	72	28	
VC321	10	26	89	36	

INDUSTRIAL HEAVY-DUTY ALUMINUM 2-WAY PLATFORM STEPLADDERS (AMP1500 SERIES)

CSA Grade 1A, ANSI Type 1A, 300-lb. Load Rating

- Durable "C" channel side rails
- Large, safe and comfortable slip-resistant platform, 14 2/5" x 17 1/10"
- Top rail guard height is 21" above platform
- Wide 3" slip-resistant serrated aluminum steps for safe climbing
- Double-rivet step construction
- Heavy-duty slip-resistant safety shoes
- Rugged outside zinc-coated steel spreader arms

VD422



Louisville
LADDER

Model No.	Nominal Height'	Open Height"	Platform Height"	Base Width"	Base Depth"	Wt. lbs.	Price /Each
VD422	6	69 5/8	48	25 3/8	53 3/8	35	
VD423	8	92 1/2	72	28 3/8	69 1/2	56	
VD424	10	114 7/8	96	31 3/8	85	77	
VD425	12	136 1/4	120	34 3/8	100 1/4	98	

EXTRA WIDE HEAVY-DUTY INDUSTRIAL ALUMINUM PLATFORM STEPLADDERS (3500-XW SERIES)

CSA grade 1A,

ANSI type 1A, 300-lb. load rating

- Large, safe and comfortable slip-resistant platform, 24" W x 18" D
- 3" wide slip-resistant serrated aluminum steps for safe climbing
- Rugged outside zinc-coated steel spreader arms
- Heavy-duty slip-resistant safety boots

VC711



FEATHERLITE
INDUSTRIAL LADDERS

Model No.	Nominal Height'	Open Height"	Platform Height"	Base Width"	Base Depth"	Weight lbs.	Price /Each
VC709	4	46	23	25	35	16	
VC710	5	56	34	27	39	20	
VC711	6	68	46	28	48	24	
VC712	8	90	68	30	53	29	

SAFETY TIPS

- Fully open the stepladder and firmly lock both spreaders
- Position the ladder so you can face your work and do not have to lean sideways



- Be sure that all ladder feet are on firm, level ground. Don't place a ladder on slippery surfaces or place loose materials underneath a ladder. Solid footing is necessary for safe ladder use

