

AIR FLUX CHIPPERS & NEEDLE SCALERS

- Lightweight compact design permits increased operator efficiency
- Paddle style trigger offers better speed control and precision
- Low noise, low vibration
- Durability and longer life

TLZ133

- Overall length: 10 1/4"
- Weight: 4.1 lbs.
- Comes with 35 mm flat chisel

- **Available accessories:** TLZ134 – 20 mm flat chisel
TLZ135 – 35 mm flat chisel
TLZ136 – moil point

TLZ131

- Overall length: 16"
- Weight: 6.1 lbs.
- Comes with 19 needles
- Replacement needles TLZ132



Model No	Stroke		Blows per minute BPM	Average Air Consumption CFM	Air Inlet	Hose Size		Vibrations Less Than m/s ²	Sound Pressure Level dB(A)	Price /Each
	in	mm				in	mm			
TLZ133	1-1/2	38	4400	9	1/4" – 18 NPT	3/8	9.5	10.2	92	
TLZ131	1-1/2	38	4000	9	1/4" – 18 NPT	3/8	9.5	10.2	104.3	

WELD FLUX CHIPPERS & NEEDLE SCALERS

- For removing rust, scale, paint & medium duty weld flux removal
- Simple plate valve design allows for smooth throttling
- Heat-treated piston, cylinder sleeve and chisel bushing for long life
- Removal of needle attachment converts tool to a weld flux chipper

- Model No.** TLZ158
- Mfg. No.** CP7120
- Bore** 1 1/8"
- Blows per minute** 4800 BPM
- Shank** 1/2 sq.in.
- Length** 18"
- Weight** 6.2 lb
- Air Flow** 15.5 CFM
- Min. Hose Size** 3/8"
- Air Inlet** 1/4" NPT
- Sound Level** 99 dBA
- Sound Power** 110 dBA
- Vibration Level** 9.7 m/s²
- Price/Each** \$

- Kit Includes:**
- 1 x Tool Body
 - 1 x 19 needles
 - 1 x 35 mm chisel



INDUSTRIAL CHIPPERS/SCALERS

- For industrial use
- Powerful
- Durable



Model No.	Mfg. No.	Bore		Stroke		Shank"	Blows Per Minute	Weight		Air Consumption At Free Speed		Air Inlet Thread"	Hose I.D."	Price /Each
		in.	mm	in.	mm			lbs.	kg	CFM	L/s			
TCW253	CP9356NS	0.71	18.0	1.18	30.0	ISO 1/2 square	3800	3.3	1.5	3.0	1.4	1/4	5/16	
TCW235	CP9356WF	0.93	23.5	1.40	35.6	ISO 1/2 square	3000	4.4	2.0	5.5	2.6	1/4	3/8	

Chisel not included