

PLUMBING FIXTURES



M-BITION® CENTRESET FAUCET

- Durable, quarter turn ceramic 1224 cartridge
- Vandal-resistant torque screw discourages tampering
- Handles feature hot and cold colour indicators
- Designed to be installed through two 1" minimum diameter holes (model **PUM076**: 4" on centre; model **PUM077**: 2" on centre)
- Drain not included
- Material: Chrome
- Type: Traditional
- Mount Location: Deck Mounted
- No. of Handles: 2
- Handle Type: Lever
- Handle Length: 4"
- Flow Rate: 1.2 GPM
- Connection Type: 1/2" IPS
- Certifications: CSA B125.1
- Manufacturer's Warranty: 5 Year Limited



M-BITION® CENTRESET FAUCET

- 1255° Duralast® ceramic cartridge designed to offer the smooth feel and reliable operation of a new faucet from the first time you use it to the last
- Vandal-resistant hex screw discourages tampering
- Brass construction, adjustable temperature limit-stops provide anti-scalding protection
- Drain not included
- Designed to be installed through three 1" diameter holes, 2" on centre
- Material: Chrome
- Type: Traditional
- Mount Location: Deck Mounted
- No. of Handles: 1
- Handle Type: Lever
- Flow Rate: 1.2 GPM
- Connection Type: 1/2" IPS
- Certifications: CSA B125.1
- Manufacturer's Warranty: 5 Year Limited
- Maximum Deck Thickness: 1-3/4"



MOEN®

Model No.	Mfg. No.	Description	Installation Holes	Overall Height"	Aerator Height"	Price /Each
PUM076	8800	Lavatory	2	4-5/8	2.28	
PUM077	8798	Kitchen	3	6-21/32	5.75	

MOEN®

Model No.	Mfg. No.	Description	Installation Holes	Overall Height"	Aerator Height"	Price /Each
PUM075	8430	Lavatory	3	3	2	

M-DURA™ LAVATORY FAUCET

- Ceramic disc cartridge with temperature limit stop
- Solid cast brass construction
- Vandal-resistant hex screw discourages tampering
- Brass construction, adjustable temperature limit-stops provide anti-scalding protection
- Temperature controlled through 110° arc of handle
- Model **PUM080**: Designed to be installed through three 1" diameter holes
- Model **PUM079**: Designed to be installed through one 1-3/8" minimum diameter hole
- Material: Chrome
- Type: Traditional
- Mount Location: Deck Mounted
- No. of Handles: 1
- Handle Type: Lever
- Flow Rate: 2.2 GPM
- Connection Type: 1/2" IPS
- Certifications: CSA B125.1
- Manufacturer's Warranty: 5 Years Against Material or Manufacturing Defects
- Maximum Deck Thickness: 1-1/8"



M-DURA™ CENTRESET FAUCET

- Heavy-duty, quarter turn ceramic disc cartridge with a durable brass shell features internal stops to prevent misalignment, ensuring complete shut-off every time
- Solid cast brass construction
- Vandal-resistant torque screw discourages tampering
- Handles feature hot and cold colour indicators
- Designed to be installed through two 1" minimum diameter holes, 4" centreset
- Material: Chrome
- Type: Traditional
- Mount Location: Deck Mounted
- Installation Holes: 2
- Overall Height: 4-1/2"
- No. of Handles: 2
- Handle Type: Lever
- Flow Rate: 2.2 GPM
- Connection Type: 1/2" IPS
- Certifications: CSA B125.1
- Manufacturer's Warranty: 5 Year Limited



MOEN®

Model No.	Mfg. No.	Description	Installation Holes	Overall Height"	Aerator Height"	Price /Each
PUM078	8413	Centreset	3	6-5/8	2.5	
PUM079	8417	Single Mount	1	6-3/4	2.5	

MOEN®

Model No.	Mfg. No.	Description	Installation Holes	Overall Height"	Aerator Height"	Price /Each
PUM080	8210	Lavatory	2	4-1/2	2	
PUM081	8215	Lavatory	2	4-1/2	2.88	

M-DURA™ WIDESPREAD FAUCET

- Heavy-duty, quarter turn ceramic disc cartridge with a durable brass shell features internal stops to prevent misalignment, ensuring complete shut-off every time
- Solid cast brass construction
- Vandal-resistant torque screw discourages tampering
- Handles feature hot and cold indicators
- Designed to be installed through three 1-9/32" minimum diameter holes, 8" widespread
- Material: Chrome
- Type: Traditional
- Mount Location: Deck Mounted
- No. of Handles: 2
- Handle Type: Lever
- Flow Rate: 2.2 GPM
- Connection Type: 1/2" IPS
- Certifications: CSA B125.1
- Manufacturer's Warranty: 5 Year Limited



COMMERCIAL SINGLE MOUNT FAUCET

- 1255° Duralast® ceramic cartridge designed to offer the smooth feel and reliable operation of a new faucet from the first time you use it to the last
- Vandal-resistant hex screw discourages tampering
- Red and blue plastic temperature indicators on handle
- Temperature controlled by 100° arc of handle travel
- Designed to be installed through one 1-1/4" minimum diameter hole
- Material: Chrome
- Type: Traditional
- Mount Location: Deck Mounted
- No. of Handles: 1
- Handle Type: Lever
- Flow Rate: 1.2 GPM
- Connection Type: 3/8" Compression
- Certifications: CSA B125.1
- Manufacturer's Warranty: 5 Year Limited



MOEN®

Model No.	Mfg. No.	Description	Installation Holes	Overall Height"	Aerator Height"	Price /Each
PUM082	8220	Lavatory	3	4-3/16	2.88	
PUM083	8228	Lavatory	3	4-3/4	2.88	

MOEN®

Model No.	Mfg. No.	Description	Installation Holes	Overall Height"	Aerator Height"	Price /Each
PUM085	9480	Lavatory	1	6-1/8	2.54	